

Axle Model	Ratings		Ratios	Axle Shaft			Nominal Ring Gear Diameter in. [mm]	Axle Housing			Spindle Type	Options			
	Max. GAW lbs. [kg]	Max. GCW HWY lbs. [kg]		Body Diameter in. [mm]	Number of Splines	Spline Diameter in. [mm]		Box Section Width in. [mm]	Box Section Height in. [mm]	Wall Thickness at Spring Seat in. [mm]		SelecTTrac™	Differential Lock	Electromagnetic Retarder	No Spin Differential
S21-172	21,000 [9,525]	100,000 [45,359]	3.07, 3.21, 3.42, 3.58, 3.73, 3.91, 4.10, 4.30, 4.56, 4.78, 5.25, 5.38, 5.57, 6.14, 6.83	2.06 [52]	46	2.35 [60]	17.3 [440]	4.61 [117]	5.24 [134]	0.43 [11]	R				
S23-172	23,000 [10,433]		3.07, 3.21, 3.42, 3.58, 3.73, 3.91, 4.10, 4.30, 4.56, 4.78, 5.25, 5.38, 5.57, 6.14												
S25-172	25,000 [11,340]		3.07, 3.21, 3.42, 3.58, 3.73, 3.91, 4.10, 4.30, 4.56, 4.78, 5.25, 5.38, 5.57, 6.14, 6.83, 7.17, 7.83	2.25 [57]											

Rating is subject to Dana engineering application approval

